

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : **Klean Power**
 Product code : 0272

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Floor Cleaner

1.3. Details of the supplier of the safety data sheet

Chemco Products Company
 19402 Susana Rd.
 Rancho Dominguez, CA 90221 - USA
 T 800-266-2116 - F 310-631-7496
<http://www.flo-kem.com>

1.4. Emergency telephone number

Emergency number : CHEMTEL: 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Corr. 1B H314
 Eye Dam. 1 H318
 STOT SE 3 H335

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms :



Signal word :

Danger

Hazard statements :

Causes severe skin burns and eye damage.
 Causes serious eye damage.
 May cause respiratory irritation.

Precautionary statements :

Do not breathe dust.
 Wash hands and forearms thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear eye protection, face protection, protective clothing, protective gloves.
 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center or doctor/physician.
 Call a POISON CENTER or doctor/physician if you feel unwell.
 Wash contaminated clothing before reuse.
 Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Dispose of contents/container in accordance with Local, State, and Federal regulations.

2.3. Hazard not otherwise classified (HNOC)

No additional information available.

Klean Power

Safety Data Sheet

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable.

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS US classification
sodium carbonate	(CAS-No.) 497-19-8	70 - 75	Eye Irrit. 2A, H319
disodium metasilicate, pentahydrate	(CAS-No.) 10213-79-3	20 - 25	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 STOT SE 3, H335
benzenesulfonic acid, C10-16-alkyl derivs., sodium salt/(Alternate sodium dodecyl benzene sulfonate)	(CAS-No.) 68081-81-2/(Alternate CAS#25155-30-0)	1 - 5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Burns to the gastric/intestinal mucosa. Abdominal pain. Gastrointestinal complaints.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Extinguishing media for surrounding fires. Adapt extinguishing media to the environment.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity	: Reacts violently with (some) acids. Reacts with (strong) oxidizers. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen).
------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: No additional information available.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Isolate from fire, if possible, without unnecessary risk.
------------------	---

Klean Power

Safety Data Sheet

6.1.1. For non-emergency personnel

Protective equipment	: Protective goggles. Protective gloves. Protective clothing. Respiratory protection.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the solid spill. If reacting: dilute toxic gas/vapor with water spray.
Methods for cleaning up	: Collect the spill only if it is in a dry state. Wetted substance: cover with powdered limestone or dry sand, earth, vermiculite. Minimize generation of dust. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Store away from other materials. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Do not get in eyes, on skin, or on clothing. Do not breathe dust. Ensure good ventilation of the work station. Observe normal hygiene standards. Provide local exhaust or general room ventilation. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required.
Hygiene measures	: Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and forearms thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation. Comply with applicable regulations.
Incompatible products	: Acids. Oxidizing agent.
Storage area	: Store in a cool, dry well-ventilated area. Keep container tightly closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No data available

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
Other information	: Do not eat, drink or smoke during use.
Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: Yellow
Odor	: Pine
Odor threshold	: No data available

Klean Power

Safety Data Sheet

pH	: No data available
pH (1%) solution	: 11.5 - 12.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Vapor pressure	: No data available
Vapor density	: No data available

Specific Gravity @ 77° F	: No data available
Solubility	: Soluble in water
Partition Coefficient n-Octanol-Water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available

9.2. Other information

VOC content	: 0 g/l
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with (some) acids. Reacts with (strong) oxidizers. Reacts with (some) metals and their compounds: release of highly flammable gases/vapors (hydrogen).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids. Contact with halogenated compounds may liberate toxic gas.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Oxidizers. May be corrosive to metals.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Phosphorus oxides. Sulfur oxides. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
----------------	------------------

disodium metasilicate, pentahydrate (10213-79-3)	
LD50 oral rat	847 mg/kg
ATE US (oral)	847 mg/kg body weight
sodium carbonate (497-19-8)	
LD50 oral rat	2800 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value)
ATE US (oral)	2800 mg/kg body weight
benzenesulfonic acid, C10-16-alkyl derivs., sodium salt/(Alternate sodium dodecyl benzene sulfonate) (68081-81-2/(Alternate CAS#25155-30-0))	
ATE US (oral)	500 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified

Klean Power

Safety Data Sheet

Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met.
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Harmful if swallowed. Burns to the gastric/intestinal mucosa. Abdominal pain. Gastrointestinal complaints.

SECTION 12: Ecological information

12.1. Toxicity

disodium metasilicate, pentahydrate (10213-79-3)	
LC50 fish 1	210 mg/l (96 h; Brachydanio rerio; Anhydrous form)
EC50 Daphnia 1	216 mg/l (96 h; Daphnia magna; Anhydrous form)
LC50 fish 2	2320 mg/l (96 h; Gambusia affinis; Anhydrous form)
EC50 Daphnia 2	632 mg/l (96 h; Lymnaea sp.; Anhydrous form)
sodium carbonate (497-19-8)	
LC50 fish 1	300 mg/l (96 h; Lepomis macrochirus)
EC50 Daphnia 1	< 424 mg/l (48 h; Daphnia magna)
EC50 other aquatic organisms 1	14 mg/l (168 h; Plankton)
LC50 fish 2	740 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 2	265 mg/l (48 h; Daphnia magna)
TLM fish 1	300 ppm (96 h; Lepomis macrochirus)
TLM other aquatic organisms 1	500 ppm (96 h; Daphnia magna)
Threshold limit algae 1	242 mg/l (5 days; Algae)

12.2. Persistence and degradability

disodium metasilicate, pentahydrate (10213-79-3)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
sodium carbonate (497-19-8)	
Persistence and degradability	Biodegradability: not applicable. Low potential for absorption in soil.
ThOD	Not applicable (inorganic)

12.3. Bioaccumulative potential

disodium metasilicate, pentahydrate (10213-79-3)	
Bioaccumulative potential	No bioaccumulation data available.
sodium carbonate (497-19-8)	
Log Pow	-6.19 (Estimated value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Other adverse effects

Other information : Avoid release to the environment.

Klean Power

Safety Data Sheet

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with Local, State, and Federal regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN Number

UN-No.(DOT) : UN3262
Other information : Under 49 CFR 173.154(c) and (b)(2): This product may be shipped as ORM-D or Limited Quantity if the inner packagings do not exceed 5 L (1.3 gallons) or 5.0 kg (11 lbs). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : UN3262, Corrosive Solid, Basic, Inorganic, N.O.S. (Disodium Trioxosilicate), 8, PGIII
Hazard labels (DOT) : 8 - Corrosive



SECTION 15: Regulatory information

15.1. US Federal regulations

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

disodium metasilicate, pentahydrate (10213-79-3)

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

sodium carbonate (497-19-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

benzenesulfonic acid, C10-16-alkyl derivs., sodium salt/(Alternate sodium dodecyl benzene sulfonate) (68081-81-2/(Alternate CAS#25155-30-0))

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

15.2. International regulations

CANADA

EU-Regulations

No additional information available.

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

disodium metasilicate, pentahydrate (10213-79-3)

Disodium metasilicate, pentahydrate the anhydrous form of this material is listed on the EPA TSCA inventory under the CAS no. 6834-92-0.

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

Klean Power

Safety Data Sheet

SECTION 16: Other information

Abbreviations Legend:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data. The information and recommendations are presented in good faith and believed to be from reliable sources, however, the information is provided without any warranty, expressed or implied, regarding its completeness or accuracy. Some information is from sources other than direct test data on the material itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product.

ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE (310) 632-7124

Revision date: 10/29/2020

Supersedes: 09/15/2020

Version: 1.2