

TECHNICAL DATA SHEET

LOW FOAM CLEANER 0735

DESCRIPTION: **LOW FOAM CLEANER 0735** is a heavy-duty low foaming cleaner formulated principally for use in automatic power scrubber and vacuum floor machines. It is also recommended for manual cleaning and mopping of floor surfaces or other surfaces where low foaming is desired. **LOW FOAM CLEANER 0735** was especially formulated for cleaning of cement floors in meat, poultry, dairy and other food processing industries. It is designed to remove black tire marks, oils, and other stubborn hard to clean stains in manufacturing plants and warehouses.

PHYSICAL PROPERTIES:

Odor.....	Butyl
Color	Clear yellow
pH of 1% Solution	12.7 - 13.7
Rinsing Ability	Excellent, complete
Foaming	Low
Weight	9.09 lbs. per gallon
Flash Point	>200°F
Specific Gravity	1.080 - 1.100

USE CONCENTRATIONS: **Light Duty:** 1 - 40 to 100 - 1 depending on soil level. This will remove standard soils including food spillage and oil drippage from tow motors, etc.

Medium Duty: 1 - 20 to 1 - 40 for factory cleaning of oils or grease from floors.

METHOD OF USE: Use with an automatic scrubbing machine or apply with a mop. Allow solution to dwell for several minutes for good penetration. Rinse with clear water.

REMARKS: Protect from freezing. If frozen, allow to warm up and mix well before using to re-dissolve crystallized deposits.

SAFETY: **LOW FOAM CLEANER 0735** contains alkaline material. Do not get into eyes or on skin or clothing. Do not take internally. In case of contact, immediately flush with water. If irritation continues, get medical attention.