

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : **Super Heavy Duty Stripper**
 Product code : 11328

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Concentrated Liquid Cleaner

1.3. Details of the supplier of the safety data sheet

Flo-Kem
 19402 Susana Rd.
 Rancho Dominguez, CA 90221 - USA
 T 310-632-7124 - F 310-631-7496
<http://www.flo-kem.com>

1.4. Emergency telephone number

Emergency number : CHEMTEL: 800-255-3924

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227
 Skin Corr. 1C H314
 Eye Dam. 1 H318

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms :



GHS05

Signal word : Danger

Hazard statements : Combustible liquid.
 Causes severe skin burns and eye damage.
 Causes serious eye damage.

Precautionary statements : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not breathe mist, vapors.
 Wash hands and forearms thoroughly after handling.
 Wear eye protection, face protection, protective clothing, protective gloves, protective boots.
 If swallowed: rinse mouth. Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Immediately call a poison center or doctor/physician.
 Specific treatment (see the emergency and first aid section of this Safety Data Sheet on this label).
 Wash contaminated clothing before reuse.
 In case of fire: Use alcohol resistant foam, BC-powder, carbon dioxide (CO2), sand to extinguish.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

Super Heavy Duty Stripper

Safety Data Sheet

2.3. Hazard not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

3.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
3.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
3.6% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
2-butoxyethanol	(CAS-No.) 111-76-2	15 - 20	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
benzyl alcohol	(CAS-No.) 100-51-6	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332
2-aminoethanol	(CAS-No.) 141-43-5	5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314
Decyl alcohol, ethoxylated, phosphated	(CAS-No.) 52019-36-0	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
sodium xylenesulfonate	(CAS-No.) 1300-72-7	1 - 5	Skin Irrit. 2, H315 STOT SE 3, H335
potassium hydroxide	(CAS-No.) 1310-58-3	1 - 5	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318
oxirane, methyl-, polymer with oxirane, ether with 2,2-(oxidoimino)bis(ethanol) (2:1), N-(3-(C9-11-isoalkyloxy)propyl) derivs., C10	(CAS-No.) 218141-49-2	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

(NOTE: If component displays the * (asterisk) symbol, the following statement applies.)

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. Immediately call a poison center or doctor/physician.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a poison center or doctor/physician.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Causes severe skin burns and eye damage.
Symptoms/effects after inhalation	: Harmful if inhaled. Corrosive to the respiratory tract.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Abdominal pain. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints. Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Super Heavy Duty Stripper

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. BC powder. Carbon dioxide. Dry chemical powder. Sand/earth.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid.
Reactivity : Reacts with (strong) oxidizers and with (some) acids. Reacts with (some) halogen compounds.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.
Other information : Although product has a flash point <200° F, it is an aqueous solution and does not sustain combustion.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Isolate from fire, if possible, without unnecessary risk.

6.1.1. For non-emergency personnel

Protective equipment : Protective goggles.
Protective gloves.
Protective clothing.
Respiratory protection.
Protective boots.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dilute combustible/toxic gases/vapors with water spray.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Wash down leftovers with plenty of water.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe mist, vapors. Ensure good ventilation of the work station. Provide good ventilation in process area to prevent formation of vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Observe normal hygiene standards. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and forearms thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Incompatible products : Strong acids. Oxidizing agent.
Storage area : Store in a cool, dry well-ventilated area. Keep container tightly closed when not in use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Super Heavy Duty Stripper

Safety Data Sheet

2-butoxyethanol (111-76-2)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	97 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	20 ppm

2-aminoethanol (141-43-5)		
ACGIH	ACGIH TWA (ppm)	3 ppm
ACGIH	ACGIH STEL (ppm)	3 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	0.46 ppm

potassium hydroxide (1310-58-3)		
ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

8.2. Exposure controls

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or face shield.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. In case of insufficient ventilation, wear suitable respiratory equipment.
Other information	: Do not eat, drink or smoke during use.
Appropriate engineering controls	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Clear red orange
Odor	: Floral
Odor threshold	: No data available
pH	: 13 - 14
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 140 °F
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Vapor pressure	: No data available
Vapor density	: No data available
Specific Gravity @ 77° F	: 1.005 - 1.025
Solubility	: Soluble in water
Partition Coefficient n-Octanol-Water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available

9.2. Other information

VOC content	: < 300 g/l CARB VOC
-------------	----------------------

Super Heavy Duty Stripper

Safety Data Sheet

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers and with (some) acids. Reacts with (some) halogen compounds.

10.2. Chemical stability

Stable under recommended conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Extremely high or low temperatures. Heat. Open flame. Sparks.

10.5. Incompatible materials

Strong acids. Oxidizers. Halogenated organic solvents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors. Sulfur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	3346 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE US (oral)	3346 mg/kg body weight

2-butoxyethanol (111-76-2)	
LD50 oral rat	530 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; 1746 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
ATE US (oral)	530 mg/kg body weight
ATE US (dermal)	435 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	2.17 mg/l/4h
ATE US (dust, mist)	2.17 mg/l/4h

2-aminoethanol (141-43-5)	
LD50 oral rat	1720 mg/kg (Rat)
LD50 dermal rabbit	1018 mg/kg (Rabbit)
ATE US (oral)	1720 mg/kg body weight
ATE US (dermal)	1018 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

potassium hydroxide (1310-58-3)	
LD50 oral rat	333 mg/kg (Rat; Equivalent or similar to OECD 425; Experimental value)
ATE US (oral)	333 mg/kg body weight

benzyl alcohol (100-51-6)	
LD50 oral rat	1620 mg/kg (Rat; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg (Rabbit; Experimental value)
ATE US (oral)	1620 mg/kg body weight
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: 13 - 14

Serious eye damage/irritation : Causes serious eye damage.
pH: 13 - 14

Super Heavy Duty Stripper

Safety Data Sheet

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
	Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

2-butoxyethanol (111-76-2)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
	Based on available data, the classification criteria are not met

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : Not classified

Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful if inhaled
Symptoms/effects after inhalation	: Harmful if inhaled. Corrosive to the respiratory tract.
Symptoms/effects after skin contact	: Causes burns/corrosion of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage.
Symptoms/effects after ingestion	: Abdominal pain. Burns to the gastric/intestinal mucosa. Gastrointestinal complaints. Nausea.

SECTION 12: Ecological information

12.1. Toxicity

sodium xylenesulfonate (1300-72-7)	
LC50 fish 1	> 1580 mg/l (Rainbow trout)
EC50 Daphnia 1	> 1020 mg/l
ErC50 (algae)	758 mg/l
NOEC chronic algae	240 mg/l

2-butoxyethanol (111-76-2)	
LC50 fish 1	116 ppm (96 h; Cyprinodon variegatus; Nominal concentration)
EC50 Daphnia 1	1700 mg/l (48 h; Daphnia sp.; Nominal concentration)
LC50 fish 2	1341 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	1720 mg/l (24 h; Daphnia magna)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	900 mg/l (168 h; Scenedesmus quadricauda)
Threshold limit algae 2	35 mg/l (192 h; Microcystis aeruginosa)

2-aminoethanol (141-43-5)	
LC50 fish 1	150 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	140 mg/l (24 h; Daphnia magna)
LC50 fish 2	329.16 mg/l (96 h; Lepomis macrochirus)
TLM fish 1	100 - 1000,96 h; Pisces
TLM other aquatic organisms 1	100 - 1000,96 h
Threshold limit algae 1	0.97 mg/l (192 h; Scenedesmus quadricauda; Inhibitory)
Threshold limit algae 2	35 mg/l (72 h; Algae)

potassium hydroxide (1310-58-3)	
LC50 fish 1	> 28.6 mg/l (96 h; Pisces; Lethal)
LC50 fish 2	80 mg/l (Gambusia affinis)
TLM fish 1	80 ppm (24 h; Gambusia affinis)

benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (96 h; Pimephales promelas; Nominal concentration)
EC50 Daphnia 1	400 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	10 ppm (96 h; Lepomis macrochirus)
EC50 Daphnia 2	230 mg/l (48 h; Daphnia magna)

Super Heavy Duty Stripper

Safety Data Sheet

benzyl alcohol (100-51-6)	
Threshold limit other aquatic organisms 1	< 658 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	640 ppm (96 h; Scenedesmus quadricauda)
Threshold limit algae 2	2600 mg/l (72 h; Algae)

12.2. Persistence and degradability

sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	Biodegradability in water: no data available.

2-butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O ₂ /g substance
Chemical oxygen demand (COD)	2.2 g O ₂ /g substance
ThOD	2.305 g O ₂ /g substance
BOD (% of ThOD)	0.31 % ThOD

2-aminoethanol (141-43-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil.
Biochemical oxygen demand (BOD)	0.8 g O ₂ /g substance
Chemical oxygen demand (COD)	1.34 g O ₂ /g substance
ThOD	2.49 g O ₂ /g substance
BOD (% of ThOD)	0.32 % ThOD

potassium hydroxide (1310-58-3)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

benzyl alcohol (100-51-6)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test) data on mobility of the substance available.
Biochemical oxygen demand (BOD)	1.6 g O ₂ /g substance
Chemical oxygen demand (COD)	2.4 g O ₂ /g substance
ThOD	2.5 g O ₂ /g substance

12.3. Bioaccumulative potential

sodium xylenesulfonate (1300-72-7)	
Bioaccumulative potential	No bioaccumulation data available.

2-butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2-aminoethanol (141-43-5)	
Log Pow	-1.91
Bioaccumulative potential	Bioaccumulation: not applicable.

potassium hydroxide (1310-58-3)	
Bioaccumulative potential	Bioaccumulation: not applicable.

benzyl alcohol (100-51-6)	
Log Pow	1.05 (Experimental value; Other; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with Local, State, and Federal regulations.
Ecology - waste materials : Avoid release to the environment.

Super Heavy Duty Stripper

Safety Data Sheet

SECTION 14: Transport information

14.1. UN Number

UN-No.(DOT) : 1760
Other information : Under 49 CFR 173.154(c) and (b)(2): This product may be shipped as ORM-D or Limited Quantity if the inner packagings do not exceed 5 L (1.3 gallons) or 5.0 kg (11 lbs). This provision does not apply to transportation by vessel or aircraft, except where other means of transportation is impracticable.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : UN1760, Corrosive Liquids, N.O.S. (Monoethanolamine, Potassium Hydroxide), 8, PGIII
Hazard labels (DOT) : 8 - Corrosive



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

sodium xylenesulfonate (1300-72-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
2-butoxyethanol (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
2-aminoethanol (141-43-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
oxirane, methyl-, polymer with oxirane, ether with 2,2-(oxidoimino)bis(ethanol) (2:1), N-(3-(C9-11-isoalkyloxy)propyl) derivs., C10 (218141-49-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Decyl alcohol, ethoxylated, phosphated (52019-36-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
potassium hydroxide (1310-58-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
RQ (Reportable quantity, section 101(14) of CERCLA as published on EPA's List of Lists) :	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
benzyl alcohol (100-51-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Fire hazard Delayed (chronic) health hazard

Super Heavy Duty Stripper

Safety Data Sheet

15.2. International regulations

CANADA

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

Prop 65 Disclaimer :

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

SECTION 16: Other information

Abbreviations Legend:

H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data. The information and recommendations are presented in good faith and believed to be from reliable sources, however, the information is provided without any warranty, expressed or implied, regarding its completeness or accuracy. Some information is from sources other than direct test data on the material itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and for this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use, or disposal of the product.

ALL NON-EMERGENCY QUESTIONS SHOULD BE DIRECTED TO CUSTOMER SERVICE (310) 632-7124

Revision date: 08/08/2018

Supersedes: 04/12/2018

Version: 2.1