

TECHNICAL DATA SHEET

FL9096 STAR BRITE 25 SEALER-FINISH

DESCRIPTION: **STARBRITE 25 SEALER-FINISH** is a high-solids floor finish that has clarity and long-lasting durability. This product is easy to apply and has exceptional spray buff or burnish response. It is ideally suited for all resilient and non-resilient flooring found in industrial, commercial, and institutional facilities. Because of its outstanding wear characteristics, it is recommended for use in schools, offices, hospitals, nursing homes, shopping centers, restaurants, and retail stores.

BENEFITS and FEATURES:

- Designed for ultra-high-speed burnishing or high-speed spray buff systems
- Flexibility to withstand repeated burnishing without film degradation
- “Wet look” gloss
- Exceptional resistance to powdering
- Long term durability
- Superior mark resistance

DIRECTIONS FOR USE: Before application, remove old finish, wax, and/or soil with a heavy-duty stripper. Rinse floor thoroughly with clean water and allow to completely dry. Apply **STARBRITE 25** in uniform, thin-to-medium coats using a clean synthetic finish mop or applicator system. For sealed floors, apply two (2) coats. For unsealed floors, apply three (3) coats. Allow each coat to thoroughly dry between coats, usually 30 to 50 minutes. It is recommended waiting 24 hours or longer before allowing heavy equipment usage. Additional coats may be applied periodically or as required to maintain finish. Deep scrub the surface prior to reapplying maintenance coats.

MAINTENANCE: Maintain by damp mopping with **NEUTRA BRITE FLOOR CLEANER** at 2 oz. per gallon. In an auto scrubber, use **NEUTRA BRITE FLOOR CLEANER** at 1 oz. per gallon. Re-coat traffic lanes on an “as required” basis. To enhance gloss in high traffic areas, spray buff or burnish using an ultra-high-speed machine.

SPECIFICATION:

Color	White Emulsion
Fragrance.....	Acrylic
pH	7.5 – 8.5
Specific Gravity.....	1.022 – 1.042
Film Color	Clear
Detergent Resistance	Excellent
Drying Time	Average of 20 minutes
Stability.....	Minimum 2 years
Coverage	1,500 – 2,000 sq. ft./gal.
Volatile Organic Compound (VOC)	CARB EXEMPT

STORAGE and HANDLING: Keep out of reach of children. Store in a cool, dry place. Avoid eye contact. Refer to the SDS for additional precautions or first aid measures. For institutional and commercial use only.